



Mobiltrans HD Series

Heavy Duty Transmission and Drivetrain Lubricants

Product Description

Mobiltrans HD 10W, 30, 50, and 60 are extra high performance, heavy duty transmission and drive-train lubricants engineered to meet or exceed the requirements of the rigorous Caterpillar TO-4 specification. This product line is uniquely designed to optimise the performance of powershift transmissions, gearboxes, and final drives. In hydraulic applications, they provide maximum protection even in high pressure systems

This technology combines selected base oils and an advanced additive system to deliver the precise performance parameters needed to maximise the productivity of construction, quarrying, and mining equipment operating in severe conditions. These products offer a clear performance advantage over the use of mixed fleet engine oils and previously used lubricants meeting Caterpillar TO-2.

Features and Benefits

Today's technology has vastly improved the performance capabilities of heavy duty earth moving equipment in terms of load, speed, control, precision, and reliability through innovative power train designs. These designs have increased the requirements of power-train fluids to deliver higher level of performance, productivity and efficiency. Friction control, wear protection, thermal stability, shear stability, rust and corrosion protection, and pumpability are features that must be optimally balanced to provide extended clutch life, slippage control, maximum drawbar loading, and high load operation even on an inclined slope at extreme temperatures. Mobiltrans HD 10W, 30, 50, 60 deliver exceptional performance in today's power train transmissions, drive trains, and hydraulic systems. The key benefits include:

Features	Advantages and Potential Benefits
Balanced static and dynamic friction coefficients	Optimised clutch-friction retention and slippage control Significantly improved clutch life compared to the best API CD/TO-2 engine oils
Compatible with modern clutch materials and elastomers	Longer clutch life and higher performance
Increased levels of anti-wear and load carrying capability	Reduced gear wear and extended life in transmissions, gearboxes, and final drives Greater productivity from reduced downtime
Excellent foam control protection	Top performance in wet brakes; excellent control of brake chatter
Excellent thermal and oxidation stability	Outstanding hydraulic oil stability and protection against high-pressure pump wear
Lower viscosities offer very good low temperature pumpability	Reduced time from start-up to production

Applications

Recommended by ExxonMobil for use in:

- Heavy duty transmissions, gear boxes, final drives, and hydraulic systems used in off-highway applications
- Off-highway industries including: mining, construction, quarrying, and agriculture
- Manual, powershift, and automatic transmissions where Allison C-4 fluids (SAE 10W and 30 grades) are called for including Twin Disc and transmissions calling for Type F fluids
- Most mobile equipment hydraulic applications

Specifications and Approvals

Mobiltrans HD meets or exceeds the requirements of the following industry and builder specifications	10W	30	50	60
Caterpillar TO-4	X	X	X	X

Mobiltrans HD Series have the following builder approvals:	10W	30	50	60
ZF TE-ML-03C	X	X		
ZF-TE-ML 07F		X		

Mobiltrans HD is recommended by ExxonMobil for use in applications requiring:	10W	30	50	60
Allison C-4	X	X		

Typical Properties

Mobiltrans HD	10W	30	50	60
SAE Grade	10W	30	50	60
Viscosity, ASTM D 445				
cSt @ 40°C	42	100	195	340
cSt @ 100°C	6.3	11.2	18.0	25.2
Viscosity Index, ASTM D 2270	96	97	100	96
Pour Point, °C, ASTM D 97	-33	-18	-15	-12
Flash Point, °C, ASTM D 92	202	224	240	244
Density @ 15°C kg/l, ASTM D 4052	0.89	0.89	0.91	0.91

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobiltrans HD are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

7-2013

Esso (Thailand) Public Company Limited
3195/17-29 Rama IV Road
Klong Tan, Klong Toey District
Bangkok 10110
Thailand

+66 2 2624 000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2014 Exxon Mobil Corporation. All rights reserved.